

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. *(Currently Amended)* A gas sensor comprising:
a sensor element formed of a solid electrolyte having an oxygen ion conductivity;
a plurality of cathodes ~~eathode~~ and an anode, each formed of a porous metal material and each formed on the sensor element, to produce a pumping current reflecting a concentration of a detection component in a measurement gas when a predetermined voltage is applied between the cathodes ~~eathode~~ and the anode, the detection component comprising oxygen, the measurement gas contacting the cathodes ~~eathode~~; and

a plurality of means for controlling a gas diffusion of the measurement gas in such a manner that the oxygen pumping current varies in accordance with a pressure of the measurement gas, the measurement gas moving from a measurement atmosphere toward the cathodes ~~eathode~~ by way of the means for controlling the gas diffusion, to thereby obtain information on the pressure of the measurement gas based on the oxygen pumping current,

wherein the cathodes are provided as different pressure dependency electrodes, each of the different pressure dependency electrodes corresponding to one of the respective means for controlling the gas diffusion; in which the means for controlling the gas diffusion are so adjusted in terms of gas diffusion resistance as to make a difference between the corresponding different pressure dependency electrodes in terms of pressure dependency of the oxygen pumping current

to be outputted; and in which the information on the pressure of the measurement gas is generated based on the oxygen pumping current outputted from each of the different pressure dependency electrodes.

2. *(Previously Presented)* The gas sensor as claimed in claim 1, in which the means for controlling the gas diffusion is a porous body having pores with bore diameters in a range from 0.01 m to 1 m.

3. *(Previously Presented)* The gas sensor as claimed in claim 2, in which the diffusion which is so controlled by the means for controlling the gas diffusion as to vary the oxygen pumping current in accordance with the pressure of the measurement gas is Knudsen diffusion.

4. *(Original)* The gas sensor as claimed in claim 3, in which the porous metal material of each of the cathode and the anode is a platinum material which is one of platinum and platinum alloy.

5. *(Previously Presented)* The gas sensor as claimed in claim 3, in which the porous metal material of the anode is a palladium material which is one of palladium and palladium alloy.

6. *(Original)* The gas sensor as claimed in claim 5, in which the oxygen pumping current corresponds to the pressure of the measurement gas substantially on one-to-one basis when the concentration of the oxygen contained in the measurement gas is constant.

7. *(Cancelled)*

8. *(Currently Amended)* The gas sensor as claimed in claim ~~[[7]]~~ 1, in which information on the concentration of the oxygen of the measurement gas, in addition to the information on the pressure of the measurement gas, is obtained based on the oxygen pumping current outputted from each of the different pressure dependency electrodes.

9. *(Currently Amended)* The gas sensor as claimed in claim ~~[[7]]~~ 1, in which the different pressure dependency electrodes comprise a first cathode and a second cathode, the outputted oxygen pumping current being more pressure dependent at the second cathode than at the first cathode, and in which a difference in the outputted oxygen pumping current between the first cathode and the second cathode is outputted as the information on the pressure of the measurement gas.

10. *(Original)* The gas sensor as claimed in claim 9, in which the outputted oxygen pumping current at the first cathode is obtained as the information on the concentration of the oxygen of the measurement gas.

11. *(Currently Amended)* The gas sensor as claimed in claim [[7]] 1, in which each of the means for controlling the gas diffusion corresponding to one of the respective cathodes is formed with a gas vent so as to introduce the measurement gas to one of the respective cathodes, and in which a diffusing power for the measurement gas is adjusted in accordance with a bore diameter of the gas vent.

12. *(Currently Amended)* The gas sensor as claimed in claim 11, in which the different pressure dependency electrodes comprise a first cathode and a second cathode, wherein the gas vent of the means for controlling the gas diffusion of the first cathode has the bore diameter in a range from 3 μm to 3,000 μm , the outputted oxygen pumping current being less pressure dependent at the first cathode than at the second cathode.

13. *(Previously Presented)* The gas sensor as claimed in claim 12, in which the diffusion at the means for controlling the gas diffusion of the first cathode is a free diffusion, and in which the oxygen pumping current detected at the gas diffusion control of the first cathode corresponds to the concentration of the oxygen of the measurement gas substantially on one-to-one basis.

14. *(Currently Amended)* The gas sensor as claimed in claim [[7]] 1, in which the gas sensor is a pressure sensor.

15. (*Original*) The gas sensor as claimed in claim 14, in which the anode of the pressure sensor is common to the plurality of the cathodes.

16. (*Currently Amended*) A sensor unit comprising a pressure sensor, the pressure sensor comprising:

a sensor element formed of a solid electrolyte having an oxygen ion conductivity;

a plurality of cathodes ~~eathode~~ and an anode, each formed of a porous metal material and each formed on the sensor element, to produce a pumping current reflecting a concentration of a detection component in a measurement gas when a predetermined voltage is applied between the cathodes ~~eathode~~ and the anode, the detection component comprising oxygen, the measurement gas contacting the cathodes ~~eathode~~; and

a plurality of means for controlling a gas diffusion of the measurement gas in such a manner that the oxygen pumping current varies in accordance with a pressure of the measurement gas, the measurement gas moving from a measurement atmosphere toward the cathodes ~~eathode~~ by way of the means for controlling the gas diffusion, to thereby obtain information on the pressure of the measurement gas based on the oxygen pumping current,

in which the sensor unit generates and outputs information on an atmospheric pressure and an altitude based on the information on the pressure obtained by the pressure sensor,

wherein the cathodes are provided as different pressure dependency electrodes, each of the different pressure dependency electrodes corresponding to one of the respective means for controlling the gas diffusion; in which the means for controlling the gas diffusion are so adjusted in terms of gas diffusion resistance as to make a difference between the corresponding different pressure dependency electrodes in terms of pressure dependency of the oxygen pumping current to be outputted; and in which the information on the pressure of the measurement gas is generated based on the oxygen pumping current outputted from each of the different pressure dependency electrodes.

17. *(Cancelled)*

18. *(Currently Amended)* The sensor unit as claimed in claim ~~[[17]]~~ 16, in which the anode of the pressure sensor is common to the plurality of the cathodes.